## Possibilities and Limits of PAT Compliant Measuring Systems for Online Determination of the Biomass Concentration

Igor Stempin <sup>1</sup>, Zoltán Kovács <sup>2</sup>, Denise Salzig <sup>1</sup>, Peter Czermak <sup>1,3,4,5</sup>

<sup>1</sup> University of Applied Sciences Mittelhessen, Institute of Bioprocess Engineering and Pharmaceutical Technology, Giessen, Germany

<sup>2</sup> Corvinus University of Budapest, Department of Food Engineering, Budapest, Hungary

<sup>3</sup> Kansas State University, Department of Chemical Engineering, Manhattan, Kansas, United States

<sup>4</sup> Justus Liebig University, Faculty of Biology and Chemistry, Giessen, Germany

<sup>5</sup> Fraunhofer Institute of Molecular Biology and Applied Ecology, Department of Bioresources,

Giessen, Germany

According to the guidelines of the PAT (Process Analytical Technology) initiative of the FDA, an improvement of the understanding of bioprocesses, and higher process reliability can be achieved through online measurement methods. In this respect insitu-procedures are especially advantageous, since they enable a contemporary measuring of a medium.

The biomass is an important process parameter, even if it is not the primarily intended product of cultivation in most industrial production applications. The cell growth is a defining parameter for the quality and efficiency of the cultivation process. The achievement of online process information in-situ is getting more and more important, but the requirements for in-situ systems are high and the technical implementation is complex. Limitations in the measurement quality arise especially in gassed systems, like aerobic cultivation processes [1, 2].

Present research reveals the possibilities and limits of different new measuring systems in aerobic cultivation processes, like the in-situ turbidimetry within near infrared zones, the focus beam reflectance measurement (FBRM) and the  $biO_2$ mass system. The  $biO_2$ mass System represents an in-house development, which correlates the biomass concentration by measuring the Oxygen Uptake Rate (OUR) in-situ [3, 4].

- [1] Beutel, S.; Henkel, S.: In situ sensor techniques in modern bioprocess monitoring. In: Applied Microbiology and Biotechnology (2011), p. 1493-1505. DOI: 10.1007/s00253-011-3470-5
- [2] Olsson, L.; Nielsen, J.: On-line and in situ monitoring of biomass in sub-merged cultivations. In: *Trends in Biotechnology* 15 (1997), p. 517–522
- [3] Stempin, I.; Kovács, Z.; Czermak, P.: Online monitoring of biomass concentration with the biO<sub>2</sub>mass sensor technology. In: AMA Science Portal - 11. Dresdner Sensor Symposium (2013), p. 414 – 417. DOI: 10.5162/11dss2013/L2
- [4] Stempin, I; Kovács, Z; Pino Grace, P; Czermak, P: (2013) Biomass O2-Sensor, Deutsche Patentanmeldung: DE102013006972.6